



FLOW METER

TM150



Series		TM150
Design		Turbine
Housing		PVC
Fitting Size	Option 1	1-1/2 inch
Fitting Type	Option 1	Schedule 40 Soc
Flow Range	GPM	10-100 GPM
	LPM	38-380 LPM
Accuracy		+/-1.5% of Reading
Repeatability		+/- .1%
Pressure Rating @ 73°	PSIG	150 PSIG
	bar	10.2 bar
Operating Temperature Range	Fahrenheit	32 to 140°F
	Celsius	0 to 60°C
Typical K Factor		210
Wetted Components	Housing	PVC
	Journal Bearings	Ceramic
	Shaft	Tungsten Carbide
	Rotor & Support	PVDF (Kynar)
	Retaining Washer	316 SS
Frequency Range		35-350 Hz @ 10-100 GPM
Strainer Size		55 mesh
Maximum Flow	GPM	100 GPM
	LPM	380 LPM
Maximum Pressure Drop in 10:1 Range	PSIG	4 PSIG
	bar	0.28 bar
Shipping Weight	lbs	1.6 lbs
	kg	0.72 kg
Power Source		Lithium Battery
Electronic Features	Feature 1	2 Totals (1 Cumulative, 1 Batch)
	Feature 2	2 Factory Cal (Gal or Ltr)
	Feature 3	1 Field Calibration
	Feature 4	Rate of Flow