

OIL METERS



LM51DN

- Gallons, litres, pints or quarts display.
- Designed with oval rotors for optimum accuracy
- **For use with:** Engine oils, transmission fluid (maximum viscosity SAE 140) or antifreeze. **Do not use with excessively dirty fluids or fluids with particles without installing a filter.**



LM50 SPECIFICATIONS

Construction	Aluminum
Type	Oval Gear
Flow Range (GPM / LPM)	0.26 to 7.8 / 1 to 30 @ 5-1,000 cps
Powered by	Lithium Battery
Accuracy	+/- 0.5% of reading
Pressure Rating	1500 PSI
Thread Size	½ in. NPT
Field Calibration	No
Display	6-digit
Units	Gallon / Litre
Warranty	1 Year

ORDERING INFORMATION

Model	Part No.
LM51DN	LM51DN



LM-200

- **Displays batch and cumulative totals in quarts**
- **For use with:** Hydraulic fluid and up to 30W oil. **Do not use with flammable fluids.**



LM-200 SPECIFICATIONS

Construction	Aluminum
Type	Mechanical, Nutating Disc
Flow Range (QPM / LPM)	16 to 80 / 15 to 76
Accuracy	+/- 2% of reading
Pressure Rating	50 PSI
Field Calibration	Yes
Display	4-digit
Units	Quarts
Warranty	1 Year


ORDERING INFORMATION

Model	Part No.	Inlet/Outlet
LM-200-Q6N	111316-04	¾ in. NPT
LM-200-Q8N	111316-01	1 in. NPT



LM-300

- **For use with:** Motor oil, gear oil, hydraulic oil, antifreeze, ATF and waste oil. **Do not use with flammable fluids or antifreeze that exceeds 50% water.**



LM-300 SPECIFICATIONS

Construction	PBT Polyester
Type	Nutating Disc
Flow Range (QPM / LPM)	8 to 80 / 7.5 to 76
Inlet/Outlet	1 in. NPT (¾ in. bushings included)
Powered By	One alkaline 9 Volt battery
Accuracy	+/- 2% of reading
Pressure Rating	50 PSI
Field Calibration	Yes
Display	6-digit
Units	Gallons, Quarts, Litres & Ounces
Warranty	1 Year

ORDERING INFORMATION

Model	Part No.
LM-300-Q6N	120000-28