FUEL TRANSFER PUMPS











EZ-8

Ideal for filling small tanks on recreational, lawn, and landscape equipment

- Gas station equivalent flowrate
- Extremely lightweight design for use on small tanks and barrels
- Self-priming low maintenance design
- Choose between direct mount or spin collar design that allows versatile mounting positions
- Thermal overload protection
- Tank adapter included (spin collar model only)

EZ-8 SPECIFICATIONS		
Flowrate (GPM / LPM)	8/30	
Voltage	12-volt DC	
Туре	Rotary Gear	
Duty Cycle (On / Off)	15 min. / 30 min.	
Power Cord	15 ft. (4.6 m) x 14/2 AWG	
Inlet / Outlet Size	¾ in. x ¾ in.	
Dispensing Hose	10 ft. (3.0 m) x 5/8 in.	
Suction Pipe	Trim-to-Fit	
Certifications	CUL) US LISTED MATTER	
Warranty	2 Year	

¾ in. Manual Nozzle	ORDERING INFORMATION		
	Model	Part No.	Mount
U.L. Listed Motor	EZ-8 (SPIN COLLAR)	137100-05	Spin Collar
	EZ-8	137100-01	Direct Mount
Diecast aluminum housing puts less stress on the tank	EZ-8 (Spin Collar) Box Contents	EZ-8 Bo	ox Contents