

FUEL TRANSFER PUMPS

25 GPM
24 VOLT



M-3425

25 GPM flowrate in a mobile fueling product.

- Great for filling large capacity tanks on equipment found in construction, agriculture, mining and logging applications
- Choose between two types of mount:
Weight centering inlet base includes pressure relief and easy strainer access
Straight base model with internal strainer
- Field-replaceable switch and vanes
- 40 amp circuit breaker motor protection

M-3425 SPECIFICATIONS

Flowrate (GPM / LPM)	25 / 95
Voltage	24-volt DC
Type	Carbon Vane
Duty Cycle (On / Off)	30 min. / 30 min.
Power Cord	15 ft. (4.6 m) of 10/3 AWG
Inlet / Outlet Size	1 in. / 1 in.
Dispensing Hose	12 ft. (3.7 m) x 1 in.
Nozzle Holder	Lockable
Certifications	
Warranty	2 Year

ORDERING INFORMATION

Model	Part No.	Nozzle	Hose	Inlet Mount
M-3425CS-P0	133262-04	None	None	Center Base
M-3425-AD	133260-02	Auto Diesel	12 ft.	Straight Base
M-3425-ML	133260-01	Manual	12 ft.	Straight Base
M-3425-P0	133260-03	None	None	Straight Base

M-3425CS-P0



M-3425-AD



M-3425-ML



M-3425-P0

