

FUEL TRANSFER PUMPS

20 GPM
115 VOLT



M-3120

20 GPM flowrate for stationary tank applications.

- Weight centering inlet base includes pressure relief and easy strainer access
- B100 models work with Biodiesel 100. B100 Fuel requires a minimum operating temperature of 40° F
- Field-replaceable switch and vanes
- Internal auxiliary temperature limiting device motor protection
- Includes 3/4 in. reducer bushing
- Cold weather (XTS) model available

M-3120 SPECIFICATIONS

Flowrate (GPM / LPM)	20 / 76
Voltage	115-volt AC
Type	Carbon Vane
Duty Cycle (On / Off)	30 min. / 30 min.
Inlet / Outlet Size	1 in. / 1 in.
Nozzle Holder	Lockable
Dispensing Hose	12 ft. (3.7 m)
Inlet Mount	Center Base
Warranty	2 Year

ORDERING INFORMATION

Model	Part No.	Nozzle	Hose	Certifications
M-3120-AD	133200-33	Auto Diesel	1 in.	UL LISTED
M-3120-AL	133200-2	Automatic	3/4 in.	
M-3120-ML	133200-34	Manual	1 in.	
M-3120-ML	133200-1	Manual	3/4 in.	
M-3120-PO	133200-07	None	None	
M-3120-PO-XTS	133200-97	None	None	
M-3120-B100-AL	133200-06	Automatic	3/4 in.	UL LISTED BKI
M-3120-B100-ML	133200-05	Manual	3/4 in.	

M-3120-AD



M-3120-AL / M-3120-B100-AL



M-3120-ML / M-3120-B100-ML



M-3120-PO

