

FUEL TRANSFER PUMPS



M-3130 & M-3295

30 GPM flowrate for stationary tank applications.

- Weight centering inlet base includes pressure relief and easy strainer access
- Field-replaceable switch and vanes
- Internal auxiliary temperature limiting device motor protection
- Cold weather (XTS) model available

SPECIFICATIONS

Flowrate (GPM / LPM)	30 / 114
Voltage	115- or 230-volt AC
Type	Carbon Vane
Duty Cycle (On / Off)	30 min. / 30 min.
Power Cord	Not Included
Inlet / Outlet Size	1 1/4 in. / 1 in.
Nozzle Holder	Lockable
Dispensing Hose	12 ft. (3.7m) x 1 in.
Inlet Mount	Center Base
Warranty	2 Year

ORDERING INFORMATION

Model	Part No.	Nozzle	Voltage	Thread	Approvals
M-3130-AD	133220-2	Auto Diesel	115/230	NPT	UL LISTED
M-3130-ML	133220-1	Manual	115/230	NPT	
M-3130-P0	133220-03	None	115/230	NPT	
M-3130-P0-XTS	133220-93	None	115/230	NPT	
M-3295-AL	133230-02	Automatic	230	BSPP	UL LISTED MOTOR CE
M-3295-ML	133230-01	Manual	230	BSPP	

