

# SPECIALTY PUMPS

**8 GPM**  
**115 VOLT**

**12 GPM**  
**115 VOLT**



PA-200H-2UR



Tote-A-Pump Assembly



## 115-Volt Chemical Pumps

### Recommended Use:

- **PA-200H-2UR:** Medium/Thick Chemicals (10 to 450 centipoise viscosity). **Do not use with gasoline, diesel fuel or micro-encapsulated chemicals.**
- **PA-120H-2UR:** Thin Chemicals (0 to 10 centipoise viscosity). **Do not use with gasoline, diesel fuel or micro-encapsulated chemicals.**

### SPECIFICATIONS

Flowrate (GPM / LPM)	8 / 30 OR 12 / 45
Voltage	115-volt AC
Type	Gear
Nozzle	Sold Separately
Duty Cycle (On / Off)	30 min. / 30 min.
Power Cord	3-Prong Grounded Plug
Inlet / Outlet Size	1 in. / 1 in.
Dispensing Hose	Sold separately
Suction Pipe	Sold separately
Housing	Plastic
Certifications	CSF
Warranty	2 Year

### ORDERING INFORMATION

Model	Part No.	Flowrate	Includes
PA-200H-2UR	118003-2	8 / 30	2-in. Union Ring
PA-200H-TAP	118602-12	8 / 30	Tote-a-Pump Assembly
PA-120H-2UR	118003-1	12 / 45	2-in. Union Ring
PA-120H-TAP	118602-11	12 / 45	Tote-a-Pump Assembly

PA-200H-2UR



PA-200H-TAP

