

SPECIALTY PUMPS

16 QPM
115/230
VOLT

32 QPM
115/230
VOLT

8 GPM
115 VOLT



L5116

115-Volt Oil Pumps

- Lightweight Design is easy to move between barrels and drums
- **For use with:** Thin to medium lubricants and up to 30W oil. **Do not use with gasoline or diesel fuel.**






L5132



PA-200-2UR

SPECIFICATIONS

Model	L5116 & L5132	PA-200-2UR
Type	Gerotor	Gear
Nozzle	3/4 in. Ball Valve	1 in. Ball Valve
Duty Cycle (On / Off)	30 min. / 30 min.	30 min. / 30 min.
Power Cord	3 ft. (.91m)	3 ft. (.91m)
Inlet / Outlet Size	1 in. / 3/4 in.	1 in. / 1 in.
Inlet Mount	Center Base	Spin Collar
Dispensing Hose	8 ft. (2.5 m) x 3/4 in.	12 ft. (3.7 m) x 1 in.
Suction Pipe	Trim-to-Fit	Telescoping to 40 in.
Housing	Aluminum	Polypropylene
Certifications	 	
Warranty	1 Year	2 Year

ORDERING INFORMATION

Model	Part No.	Flowrate	Voltage
L5116	142100-01	16 QPM / 15 LPM	115/230V AC
L5132	142100-02	32 QPM / 30 LPM	115/230V AC
PA-200-2UR	118003-11	8 GPM / 30 LPM	115V AC

L5116



L5132



PA-200-2UR

