



8 GPM
12 VOLT

12 GPM
12 VOLT



12-Volt Chemical Pumps

Recommended Use:

- **P-200H-2UR:** Medium/Thick Chemicals (10 to 450 centipoise viscosity). **Do not use with gasoline, diesel fuel or micro-encapsulated chemicals.**
- **P-120H-2UR:** Thin Chemicals (0 to 10 centipoise viscosity). **Do not use with gasoline, diesel fuel or micro-encapsulated chemicals.**

Tote-A-Pump Assembly



SPECIFICATIONS

Flowrate (GPM / LPM)	8 / 30 OR 12 / 45
Voltage	12-volt DC
Type	Gear
Nozzle	Sold Separately
Duty Cycle (On / Off)	30 min. / 30 min.
Power Cord	20 ft. (6.1 m) OR 15 ft. (4.6 m)
Inlet / Outlet Size	1 in. / 1 in.
Inlet Mount	Direct Mount
Dispensing Hose	Sold separately
Suction Pipe	Sold separately
Housing	Plastic
Certifications	
Warranty	2 Year

ORDERING INFORMATION

Model	Part No.	Flowrate	Power Cord	Includes
P-200H-2UR	118000-2	8 / 30	15 ft.	2-in. Union Ring
P-200H-TAP	118602-10	8 / 30	15 ft.	Tote-a-Pump Assembly
P-120H-2UR	118000-1	12 / 45	20 ft.	2-in. Union Ring

P-200H-2UR



P-200H-TAP Tote-a-Pump



P-120H-2UR

