



Specifically designed for use with high viscosity fluids. Consider the viscosity of the fluid being pumped and the temperature range when choosing the best oil pump for your application.

12-Volt Oil Pumps



L5016

- Lightweight Design is easy to move between barrels and drums
- Two flow rates to choose from
- **For use with:** Oil (up to 90W), waste oil, hydraulic fluid, antifreeze and non-flammable oil-based solvents. **Do not use with gasoline or diesel fuel.**



P-200-2UR

SPECIFICATIONS

Model	L5016	P-200-2UR
Part No.	142100-03	118000-9
Flowrate	16 QPM / 15 LPM	8 GPM / 30 LPM
Type	Gerotor	Gear
Nozzle	3/4 in. Ball Valve	1 in. Ball Valve
Duty Cycle (On / Off)	30 min. / 30 min.	30 min. / 30 min.
Power Cord	None	15 ft. (4.6 m) of 10/3
Inlet / Outlet Size	1 in. / 3/4 in.	1 in. / 1 in.
Inlet Mount	Center Base	Spin Collar
Dispensing Hose	8 ft. (2.5 m) x 3/4 in.	12 ft. (3.7 m) x 1 in.
Suction Pipe	Trim-to-Fit	Telescoping to 40 in.
Housing	Aluminum	Polypropylene
Certifications		
Warranty	1 Year	2 Year

L5016



P-200-2UR

