HAND PUMPS



RP-10

- Rotary action pump with lockable handle for security
- Built-in anti-siphon valve
- For Use with: Gasoline, diesel fuel, kerosene, medium oil (up to 30W) and hydraulic fluid



- Basic, rotary action pump
- For Use with: Petroleum based fluids having a flash point above 100° F. Diesel fuel and kerosene.
 Light oil (up to 10W) and hydraulic fluid.
 Do not use with gasoline.

RP-10 SPECIFICATIONS	
Flowrate (GPM / LPM)	10 / 38 per 100 Strokes
Туре	Rotary
Nozzle	Metal
Inlet / Outlet Size	1 in. / ¾ in.
Tank Fitting	2 in.
Dispensing Hose	8 ft. (2.5 m) x ¾ in. with Static Wire
Suction Pipe	Telescoping to 40 in.
Certifications	(I) LISTED
Warranty	2 Year

ORDERING INFORMATION	
Model	Part No.
RP-10-UL	123000-06



Flowrate (GPM / LPM) 8 / 30 per 90 Revolutions Type Rotary Spout Inlet / Outlet Size Tank Fitting Dispensing Hose N/A Three Piece Metals	RP-5 SPECIFICATIONS	
Nozzle Spout Inlet / Outlet Size N/A Tank Fitting 2 in. Dispensing Hose N/A	Flowrate (GPM / LPM)	8 / 30 per 90 Revolutions
Inlet / Outlet Size N/A Tank Fitting 2 in. Dispensing Hose N/A	Туре	Rotary
Tank Fitting 2 in. Dispensing Hose N/A	Nozzle	Spout
Dispensing Hose N/A	Inlet / Outlet Size	N/A
	Tank Fitting	2 in.
Continue Disco Motol	Dispensing Hose	N/A
Suction Pipe Three-Piece Metal	Suction Pipe	Three-Piece Metal
Warranty 90 Days	Warranty	90 Days

ORDERING INFORMATION	
Model	Part No.
RP-5	129003-1

